

# FIBREGLASS & RESIN SALES PTY LTD

ACN: 053 958 731  
111 KEW ST. WELSHPOOL W.A 6106  
Phone: 9470 2571  
Fax: 9361 9243

## ELASTOMER 17XT

CASTING & MOULDING COMPOUND

ELASTOMER 17XT is a two component flexible and tough Polyurethane system for use in various applications:

- for concrete and plaster
- abrasion and wear resistant linings, chutes, scraper blades etc.,
- moulded flexible articles, bumpers, metals linings, etc.,
- strong and elastic adhesive and gaskets
- potting and encapsulation

Some advantages:

- easy to process – using unskilled personnel
- mixing/processing instructions are supplied
- can be processed on site, without electricity or machinery
- economical
- 20-40 minutes pot life
- cures at room temperature and can be processed without added heat
- remains flexible even at low temperatures
- good abrasion and impact resistance
- good tear resistance
- good elongation and overall toughness
- good adhesion to many surfaces
- contains no solvent or volatile chemicals
- minimal shrinkage
- can be moulded to almost any thickness

Mix Ratio:

100 parts by weight of PART A: 25 parts by weight PART B

Processing instructions are available on request

Colour:

Black or Natural - Although natural can be coloured with a polyurethane pigment.

Storage:

Store ELASTOMER 17XT raw materials PART A and PART B under proper warehouse conditions between 20°C – away from sunlight, moisture or other materials. Under these conditions and in the original containers, the material can be stored for a minimum of 6 months.