

Material Safety Data Sheet

H60S Techniglue-CA Slow Hardener

Version 1.1



Section 1: Identification of the Substance or Mixture and of the Supplier

Trade Name : H60S Techniglue-CA Slow Hardener.

Product Code : H60S

Recommended Use : Used in conjunction with epoxy resin for adhesive and composite applications

Company : ATL Composites

Address : 12-14 Production Ave Ernest 4214

Telephone : +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

Emergency telephone number : +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

Revision Date : 19th April 2013

Section 2: Hazards Identification

Hazard Classification : HAZARDOUS SUBSTANCE. DANGEROUS GOODS

Risk Phrases

R34	Causes burns.
R43	May cause sensitisation by skin contact.

Safety Phrases

S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advise.
S28	After contact with skin, wash immediately with plenty of soap-suds.
S37/39	Wear suitable gloves and eye / face protection.

Section 3: Composition/Information on Ingredients

Chemical Name	CAS No.	Weight %
Polymer of c-18 unsat'd fatty acid dimers w/ teta & tofa	68082-29-1	30 - 60
Tetraethylenepentamine	112-57-2	<10
Polyoxyalkyleneamine	9046-10-0	<10
Polyamines	-	<10
Other ingredients determined not to be hazardous	-	To 100

Material Safety Data Sheet

H60S Techniglu-CA Slow Hardener

Version 1.1



Section 4: First Aid Measures

General advice	:	Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
Eye contact	:	Rinse immediately with plenty of water for at least 15 minutes.
Skin contact	:	Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Take off contaminated clothing and shoes immediately.
NOTE TO PHYSICIANS:		Application of corticosteroid cream has been effective in treating skin irritation.
Ingestion	:	Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side.
Inhalation	:	Move to fresh air.

Section 5: Fire Fighting Measures

Suitable extinguishing media :	Alcohol-resistant foam. Carbon dioxide (CO ₂). Dry chemical. Dry sand. Limestone powder.
Specific hazards :	May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes.
Special protective equipment for fire-fighters :	Avoid contact with the skin. Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental Release Measures

Personal precautions	Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.
Environmental precautions :	Construct a dike to prevent spreading.
Methods for cleaning up :	Approach suspected leak areas with caution. Place in appropriate chemical waste container.
Additional advice :	If possible, stop flow of product.

Section 7: Handling and Storage

Handling

Advice on safe handling :	Do not get in eyes, on skin or on clothing. Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated contact with skin, eyes and clothing. Wash thoroughly after handling. DANGER.
---------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Material Safety Data Sheet

H60S Technigluue-CA Slow Hardener

Version 1.1



Corrosive to the eyes. Corrosive to the skin. May be harmful if absorbed through the skin. May be harmful if swallowed. Causes respiratory tract irritation. May cause skin sensitization. Containers, even those that have been emptied, can contain hazardous product residues. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.

Storage

Requirements for storage areas and containers :

Keep containers closed when not in use.

Section 8: Exposure Controls / Personal Protection

Workplace exposure standards: No exposure standards have been established for product components.

Engineering measures

Provide readily accessible eye wash stations and safety showers.
Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

Personal protective equipment:

Respiratory protection :

Not required for properly ventilated areas.

Hand protection :

Neoprene gloves.
PVC disposable gloves
Butyl-rubber
Nitrile rubber.

Impervious gloves.

The breakthrough time of the selected glove(s) must be greater than the intended use period.

Eye protection :

Chemical resistant goggles must be worn.

Skin and body protection :

Long sleeve shirts and trousers without cuffs.
Impervious clothing.

Environmental exposure

Controls :

Construct a dike to prevent spreading.

Special instructions for protection and hygiene:

Discard contaminated leather articles. Provide readily accessible eye wash stations and safety showers. Wash at the end of each workshift and before eating, smoking or using the toilet. Remove contaminated clothing. Drench affected area with water for at least 15 minutes

Section 9: Physical and Chemical Properties

Form

:

Gel

Colour

:

Amber

Odour

:

Amine odour

pH

:

Not available

Material Safety Data Sheet

H60S Technigluue-CA Slow Hardener

Version 1.1



Melting Point	:	Not Determined
Boiling Point	:	>100°C
Flash Point	:	>101°C
Vapour Pressure	:	0.13mmHg
Density	:	0.98 to 1.05
Solubility in water	:	Slight (0.1-1%)

Section 10: Stability and Reactivity

Conditions to avoid	:	Extremes of temperature and direct sunlight. Exposure to water vapour.
Materials to avoid	:	Strong oxidizing agents. Strong acids.
Hazardous decomposition Products	:	Oxides of nitrogen Carbon monoxide
Hazardous reactions	:	Stable. Reacts violently with strong oxidising agents.

Section 11: Toxicological Information

Acute Health Hazard

Ingestion	:	LD50 : 2,200 mg/kg Species : Rat.
Inhalation	:	LC50 (1 h) : > 20 mg/l Species : Rat. Method Estimated. ISO TC58 (1 h) : 0 ppm Method : Estimated.
Skin.	:	No data is available on the product itself. Skin. - Components Phenol LD50 : 630 mg/kg Species : Rabbit.
Eye irritation/corrosion	:	Severe eye irritation.
Acute dermal irritation/corrosion	:	Moderate skin irritation.
Sensitization	:	May cause sensitization by skin contact. Sensitization has occurred in laboratory animals after repeated exposures.
Chronic Health Hazard	:	Results from a battery of short term genotoxicity tests on this material or its components indicate mutagenic activity. Adsorption of phenolic solutions through the skin may be very rapid and can cause death. Lesser exposures can cause damage to the kidneys, liver, pancreas and spleen, and edema of the lungs. Chronic exposures can cause death from liver and kidney damage.

Section 12: Ecological Information

Aquatic toxicity : No data is available on the product itself.
Toxicity to other organisms : No data available.
Persistence and degradability

Material Safety Data Sheet

H60S Technigluue-CA Slow Hardener

Version 1.1



Mobility : No data available.

Bioaccumulation : No data is available on the product itself.

Section 13: Disposal Considerations

Waste from residues / unused

Products : Contact supplier if guidance is required.

Contaminated packaging : Dispose of container and unused contents in accordance with federal, state, and local requirements.

Section 14: Transport Information

ROAD & RAIL TRANSPORT:

ADG U.N. Number	UN2735
ADG Proper Shipping Name	AMINES, LIQUID, CORROSIVE, N.O.S. (Tetraethylenepentamine)
ADG DG Class	8
ADG Hazchem Code	3X
ADG Packing Group	III

Other Information

IATA	Proper shipping name: Amines, liquid, corrosive, n.o.s. (Tetraethylenepentamine) Class : 8 UN/ID No. : UN2735 Packing group : III
IMDG	Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Tetraethylenepentamine) Class : 8 UN/ID No. : UN2735 Packing group : III

Section 15: Regulatory Information

The principal components and additives of this product are included in the Australian Inventory of Chemical Substances (AICS) or comply with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989.

Poisons Schedule 5

Hazard Category HAZARDOUS SUBSTANCES
CLASSIFICATION: Corrosive. Sensitiser.

Packaging & Product is labelled in accordance with the Code

Material Safety Data Sheet

H60S Techniglue-CA Slow Hardener

Version 1.1



ATL composites

Labelling of Practice for Labelling Workplace Substances.

Section 16: Other Information

Contact

Person/Point

PRODUCT INFORMATION MANAGER: (+61) 7 5563 1222
12-14 Production Av Ernest

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.